



	Safety Goggles 3M Fahrenheit™ SA, gas-tight	
Field of Application and Properties		
<ul style="list-style-type: none"> ▪ Maximum protection and wear: Type-tested and certified safety eye wear by 3M. Soft wide frame, stream-lined design, light-weight and comfortable to wear. Ideally suited for wearing over a respiratory mask. Protection against UV light. ▪ Application area: Protection against mechanical risks, liquids and coarse dust particles. ▪ Protection capacity: Suitable for particles up to 120 m/s, gas-tight. ▪ Before use: Check for any damage! Do not use goggles if marking is absent or illegible. 		
Type		
Protective Goggles SA (non-vent / gas-tight version)		
Item No.	121730	
Size	One	
Colour	Crystal blue, colourless lens	
Properties		
<ul style="list-style-type: none"> ▪ 180° field of vision with large lens made from clear acetate ▪ Mechanical rigidity up to 45 m/s (F) ▪ Special coating to provide scratch-resistance and anti-fogging ▪ Non-vent goggles, gas-tight ▪ Comfortable, easily adjustable head band (23 mm) ▪ Includes pouch for cleaning lens and storing safety goggles 		
Frame Marking		
3M	Code letter of manufacturer	
166	EN standard	
F	Impact protection up to 45 m/s	
3, 4, 9	Resistant against liquids, dust particles, molten metals, hot solids	
CE	EC conformity	
0194	Number of notified body	
Lens Marking		
3M	Code letter of manufacturer	
1	Optical class	
F	Surface resistance – small particles (45 m/s)	

9	Resistance against molten metals and hot solids
N	Resistance to fogging
EN 166	Certification
CE	EC-conformity
0194	Number of notified body
Care instructions	
<ul style="list-style-type: none"> ▪ Cleaning: Using clean water and household washing-up liquid (no lye, acids or solvents!). Avoid a strong mechanical action when cleaning (scratched surface = high proportion of stray light). ▪ Disinfection: Item can be disinfected with any standard disinfectant. 	
CE CE-Marking	
CE-marking in accordance with PPE Directive 89/686/EEC for PPE. The type test performed was based on EN 166.	
0194 Notified Body „0194“	
INSPEC International Ltd, 56 Leslie Hough Way, Salford, Greater Manchester, M6 6AJ, United Kingdom	
 Quality Management System	
Our Quality management system is tested and certified by TÜV Product Service GmbH (a certification body accredited by the German Accreditation Council) in accordance with DIN EN ISO 9001:2008. Regular audits and production site inspections guarantee the quality of our products.	
 Storage and Transport Conditions	
<ul style="list-style-type: none"> ▪ Cool (+5 to +50°C) ▪ Dry (humidity < 90%) ▪ No contact with pointed and/or sharp objects 	
Manufacturer	
3M Centre, Bracknell, Berkshire, RG12 8HT, England	
Distributor	
<div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="text-align: center;">  </div> <div style="text-align: center;"> <p>BERNER INTERNATIONAL GmbH Mühlenkamp 6 - 25337 Elmshorn Tel: 04121 4356 0 Fax: 04121 4356 20 info@berner-international.de www.berner-international.de</p> </div> </div>	