

BIOCLEAN-D™ HOOD BDHD

About

The BioClean-D™ single use three piece Hood has been designed and constructed for a perfect fit. Made from antistatic low-linting durable CleanTough™ material, the hood features an elasticated face-opening with reinforced edges for exceptional comfort and protection.

Specifications

MATERIAL:

Antistatic CleanTough™ material

COLOUR:

White

CONSTRUCTION:

Bound seams with single needle stitching

CLASSIFICATION:

PPE Cat 3 Type PB [6]

CHARACTERISTICS:

Antistatic to EN 1149-1 & low particulating

COMPATIBILITY:

ISO Class 4

Features

- Low-linting
- Durable CleanTough™ material
- Tested against permeation standard ASTM D6978-05

PPE CATEGORY 3 TYPE
PB [6]

THREE PIECE DESIGN

ANTISTATIC

LOW-LINTING &
DURABLE



Quality Standards

- Manufactured in a facility holding ISO 9001:2008 and 89/686/EEC Article 11b certifications
- Conforms to Category 3 - Complex Design Personal Protective Equipment PPE Directive 89/686/EEC
- Tested against standard EN ISO 13034 protective clothing against liquid chemicals (Type PB[6])
- Tested against standard EN ISO 14325 protective clothing against chemicals
- Tested against standard EN 1149-1 protective clothing - electrostatic properties
- Tested against permeation standard ASTM D6978-05 for cytotoxic drugs
- Processed in an NEBB certified ISO Class 4 environment

Shelf Life & Storage

Five (5) years from date of manufacture.
Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light.

Performance Test Results

TEST	RESULT		PERFORMANCE CLASS (EN 14325)
Abrasion Resistance	10 to 100 cycles		1
Flex Cracking Resistance	5,000 to 15,000 cycles		3
Trapezoidal Tear Resistance	CD 29.5 N		2
Trapezoidal Tear Resistance	MD 50.8 N		3
Tensile Strength	CD 59.4 N		1
Tensile Strength	MD 79.3 N		2
Puncture Resistance	5.9 N		2
Repellence to Liquids	30% H ₂ SO ₄	96.9%	3
	10% NaOH	98.0%	3
	O-Xylene	94.6%	2
	Butan-1-ol	95.4%	3
Penetration by Liquids	30% H ₂ SO ₄	0%	3
	10% NaOH	0%	3
	O-Xylene	0%	3
	Butan-1-ol	0%	3
Resistance to Ignition	Pass		N/A
Seam Strength ¹	103.2 N		3
Surface Resistivity	1.1 x 10 ¹⁰ Ω		N/A

¹Seam not destroyed.

Particle Shedding Test Results

TEST	RESULT	CATEGORY (IEST-RP-CC003.3)
Particle Shedding (Helmke Drum Test)	<260	Category I

CleanTough™ Material - ASTM D6978-05 Test Results

Breakthrough detection time (minutes)

Breakthrough of the test chemical is deemed to have occurred when the permeation rate has reached 0.01 µg/cm²/min

CISPLATIN	CARMUSTINE	CYCLO- PHOSPHA- MIDE	DOXO-RUBICIN HYDRO- CHLORIDE	5- FLUORO- URACIL	METHO- TREXATE	ETOPOSIDE	PACLITAXEL	THIOTEPA
>480	>480	>480	>480	>480	>480	>480	>480	>480

TO ORDER

Re-Order BDHD	Chest N/A	Height N/A	Size Universal
------------------	--------------	---------------	-------------------

Packing

30 pieces per sealed inner PE bag; one inner bag per sealed outer PE bag; six outer bags per lined carton (180 pieces)

CONTACT

Europe (Headquarters)

Nitritex Ltd.
Minton Enterprise Park,
Oaks Drive,
Newmarket, Suffolk,
CB8 7YY,
United Kingdom
T: +44 (0) 1638 663338
F: +44 (0) 1638 668890
E: europa@bioclean.com

Other Regions

Asia: malaysia@bioclean.com
Americas: americas@bioclean.com



BioClean™ is a brand of Nitritex Ltd.

For more information, please visit www.bioclean.com

BDHD/1602/PDS18

BIOCLEAN-D™ HOOD Sterile S-BDHD

About

The BioClean-D™ Hood is a sterile single use hood designed and constructed using three sections for a perfect fit. Made from antistatic durable low-linting CleanTough™ material, the hood features an elasticated face-opening with reinforced edges for exceptional comfort and protection.

Specifications

MATERIAL:

Antistatic CleanTough™ material

COLOUR:

White

CONSTRUCTION:

Bound seams with single needle stitching

CLASSIFICATION:

PPE Cat 3 Type PB [6]

CHARACTERISTICS:

Antistatic to EN1149-1 & low particulating

COMPATIBILITY:

ISO Class 4 & EU GMP Grade A

STERILIZATION:

Gamma irradiation

Features

- Low-linting
- Durable CleanTough™ material
- Tested against permeation standard ASTM D6978-05

PPE CAT 3 TYPE PB [6]

THREE PIECE DESIGN

ANTISTATIC

LOW-LINTING &
DURABLE



Quality Standards

- Manufactured in a facility holding ISO 9001:2008 and 89/686/EEC Article 11b certifications
- Conforms to Category 3 - Complex Design Personal Protective Equipment PPE Directive 89/686/EEC
- Tested against standard EN ISO 13034 protective clothing against liquid chemicals (Type PB[6])
- Tested against standard EN ISO 14325 protective clothing against chemicals
- Tested against standard EN 1149-1 protective clothing - electrostatic properties
- Tested against permeation standard ASTM D6978-05 for cytotoxic drugs
- Processed in an NEBB certified ISO Class 4 environment
- Sterilized in accordance with ISO 11137-1:2006

Performance Test Results

TEST	RESULT		PERFORMANCE CLASS (EN 14325)
Abrasion Resistance	10 to 100 cycles		1
Flex Cracking Resistance	5,000 to 15,000 cycles		3
Trapezoidal Tear Resistance	CD 29.5 N		2
Trapezoidal Tear Resistance	MD 50.8 N		3
Tensile Strength	CD 59.4 N		1
Tensile Strength	MD 79.3 N		2
Puncture Resistance	5.9 N		2
Repellence to Liquids	30% H ₂ SO ₄	96.9%	3
	10% NaOH	98.0%	3
	O-Xylene	94.6%	2
	Butan-1-ol	95.4%	3
Penetration by Liquids	30% H ₂ SO ₄	0%	3
	10% NaOH	0%	3
	O-Xylene	0%	3
	Butan-1-ol	0%	3
Resistance to Ignition	Pass		N/A
Seam Strength ¹	103.2 N		3
Surface Resistivity	1.1 x 10 ¹⁰ Ω		N/A

¹Seam not destroyed.

Sterilization

Method: Gamma irradiation
 Minimum Dose: 25kGy
 Sterility Assurance Level: 10⁻⁶

Shelf Life & Storage

Three (3) years from date of manufacture. Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light.

Particle Shedding Test Results

TEST	RESULT	CATEGORY (IEST-RP-CC003.3)
Particle Shedding (Helmke Drum Test)	<260	Category I

CleanTough™ Material - ASTM D6978-05 Test Results

Breakthrough detection time (minutes)

Breakthrough of the test chemical is deemed to have occurred when the permeation rate has reached 0.01 µg/cm²/min

CISPLATIN	CARMUSTINE	CYCLO- PHOSPHA- MIDE	DOXO-RUBICIN HYDRO- CHLORIDE	5- FLUORO- URACIL	METHO- TREXATE	ETOPOSIDE	PACLITAXEL	THIOTEPA
>480	>480	>480	>480	>480	>480	>480	>480	>480

TO ORDER

Re-Order S-BDHD	Chest N/A	Height N/A	Size Universal
--------------------	--------------	---------------	-------------------

Packing

One piece per sealed inner PE bag; 30 inner bags per sealed outer PE bag; six outer bags per lined carton (180 pieces)

CONTACT

Europe (Headquarters)

Nitritex Ltd.
Minton Enterprise Park,
Oaks Drive,
Newmarket, Suffolk,
CB8 7YY,
United Kingdom
T: +44 (0) 1638 663338
F: +44 (0) 1638 668890
E: europa@bioclean.com

Other Regions

Asia: malaysia@bioclean.com
Americas: americas@bioclean.com



BioClean™ is a brand of Nitritex Ltd.

For more information, please visit www.bioclean.com

S-BDHD/1601/PDS11