

BIOCLEAN-D™ LAB COAT BDLC

About

The BioClean-D™ single use Lab Coat offers excellent comfort and protection. The product has been carefully developed, designed and constructed from antistatic CleanTough™ material which is particularly durable and low-linting. The garment features press stud fastenings, open cuffs, three pockets and a rear vent.

Specifications

MATERIAL:

Antistatic CleanTough™ material

COLOUR:

White

CONSTRUCTION:

Bound seams with single needle stitching

CLASSIFICATION:

PPE Cat 3 Type PB [6]

CHARACTERISTICS:

Antistatic EN 1149-1 & low particulating

COMPATIBILITY:

Non-critical environments

Features

- Low-linting & durable CleanTough™ material
- Press stud fastening
- Open cuff, three pockets & rear vent



**EXCEPTIONAL
COMFORT &
PROTECTION**

PPE CAT 3 TYPE PB [6]

ANTISTATIC

**LOW-LINTING &
DURABLE**



Quality Standards

- Manufactured in a facility holding ISO 9001:2008 and 89/686/EEC Article 11b certifications
- Conforms to Category 3 - Complex Design Personal Protective Equipment PPE Directive 89/686/EEC
- Tested against standard EN ISO 13034 protective clothing against liquid chemicals (Type PB[6])
- Tested against standard EN ISO 14325 protective clothing against chemicals
- Tested against permeation standard ASTM D6978-05 for cytotoxic drugs
- Processed in an NEBB certified ISO Class 4 environment

Shelf Life & Storage

Five (5) years from date of manufacture.
Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light.

Performance Test Results

TEST	RESULT		PERFORMANCE CLASS (EN 14325)
Abrasion Resistance	10 to 100 cycles		1
Flex Cracking Resistance	5,000 to 15,000 cycles		3
Trapezoidal Tear Resistance	CD 29.5 N		2
Trapezoidal Tear Resistance	MD 50.8 N		3
Tensile Strength	CD 59.4 N		1
Tensile Strength	MD 79.3 N		2
Puncture Resistance	5.9 N		2
Repellence to Liquids	30% H ₂ SO ₄	96.9%	3
	10% NaOH	98.0%	3
	O-Xylene	94.6%	2
	Butan-1-ol	95.4%	3
Penetration by Liquids	30% H ₂ SO ₄	0%	3
	10% NaOH	0%	3
	O-Xylene	0%	3
	Butan-1-ol	0%	3
Resistance to Ignition	Pass		N/A
Seam Strength ¹	103.2 N		3
Surface Resistivity	1.1 x 10 ¹⁰ Ω		N/A

¹Seam not destroyed

Particle Shedding Test Results

TEST	RESULT	CATEGORY (IEST-RP-CC003.3)
Particle Shedding (Helmke Drum Test)	< 1700	Category I

TO ORDER

Re-Order	Chest	Height	Size
BDLC-S	84-92cm (33"-36")	164-170cm (5'4"-5'6")	Small
BDLC-M	92-100cm (36"-39")	170-176cm (5'6"-5'9")	Medium
BDLC-L	100-108cm (39"-42")	176-182cm (5'9"-6'0")	Large
BDLC-XL	108-116cm (42"-45")	182-188cm (6'0"-6'2")	X-Large
BDLC-XXL	116-124cm (45"-48")	188-194cm (6'2"-6'4")	XX-Large

Packing

One piece per sealed inner PE bag; one inner bag per sealed outer PE bag; 30 outer bags per lined carton (30 pieces)

CONTACT

Europe (Headquarters)

Nitritex Ltd.
Minton Enterprise Park,
Oaks Drive,
Newmarket, Suffolk,
CB8 7YY,
United Kingdom
T: +44 (0) 1638 663338
F: +44 (0) 1638 668890
E: europa@bioclean.com

Other Regions

Asia: malaysia@bioclean.com
Americas: americas@bioclean.com



BioClean™ is a brand of Nitritex Ltd.
For more information, please visit www.bioclean.com

BDLC/1608/PDS20

BIOCLEAN-D™ STERILE LAB COAT S-BDLC

About

The BioClean-D™ single use Sterile Lab Coat offers excellent comfort and protection. The product has been carefully developed, designed and constructed from white CleanTough™ material which is particularly durable and low-linting. The garment features press stud fastenings, open cuffs, three pockets and a rear vent.

Specifications

MATERIAL:

Antistatic CleanTough™ material

COLOUR:

White

CONSTRUCTION:

Bound seams with single needle stitching

CLASSIFICATION:

PPE Cat 3 Type PB [6]

CHARACTERISTICS:

Antistatic to EN1149-1 & low particulating

COMPATIBILITY:

Non-critical environments

STERILIZATION:

Gamma irradiation

Features

- Low-linting & durable CleanTough™ material
- Press stud fastening
- Open cuff, three pockets & rear vent



EXCEPTIONAL
COMFORT &
PROTECTION

PPE CAT 3 TYPE PB [6]

ANTISTATIC

LOW-LINTING &
DURABLE



Billy Bioclean™ represents Bioclean's™
GMP compatible disposable garments

Quality Standards

- Manufactured in a facility holding ISO 9001:2008 and 89/686/EEC Article 11b certifications
- Conforms to Category 3 - Complex Design Personal Protective Equipment PPE Directive 89/686/EEC
- Tested against standard EN ISO 13034 protective clothing against liquid chemicals (Type PB[6])
- Tested against standard EN ISO 14325 protective clothing against chemicals
- Tested against standard EN 1149-1 protective clothing - electrostatic properties
- Tested against permeation standard ASTM D6978-05 for cytotoxic drugs
- Processed in an NEBB certified ISO Class 4 environment
- Sterilized in accordance with ISO 11137-1:2006

Performance Test Results

TEST	RESULT		PERFORMANCE CLASS (EN 14325)
Abrasion Resistance	10 to 100 cycles		1
Flex Cracking Resistance	5,000 to 15,000 cycles		3
Trapezoidal Tear Resistance	MD 50.8 N		3
Trapezoidal Tear Resistance	CD 29.5 N		2
Tensile Strength	MD 79.3 N		2
Tensile Strength	CD 5.9 N		1
Puncture Resistance	5.9 N		2
Repellence to Liquids	30% H ₂ SO ₄	96.9%	3
	10% NaOH	98.0%	3
	O-Xylene	94.6%	2
	Butan-1-ol	95.4%	3
Penetration by Liquids	30% H ₂ SO ₄	0%	3
	10% NaOH	0%	3
	O-Xylene	0%	3
	Butan-1-ol	0%	3
Resistance to Ignition	Pass		N/A
Seam Strength ¹	103.2 N		3
Surface Resistivity	1.1 x 10 ¹⁰ Ω		N/A

¹Seam not destroyed.

Sterilization

Method: Gamma irradiation
 Minimum Dose: 25kGy
 Sterility Assurance Level: 10⁻⁶

Shelf Life & Storage

Three (3) years from date of manufacture. Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light.

Particle Shedding Test Results

TEST	RESULT	CATEGORY (IEST-RP-CC003.3)
Particle Shedding (Helmke Drum Test)	<1700	Category I

CleanTough™ Material - ASTM D6978-05 Test Results

Breakthrough detection time (minutes)

Breakthrough of the test chemical is deemed to have occurred when the permeation rate has reached 0.01 µg/cm²/min

CISPLATIN	CARMUSTINE	CYCLO- PHOSPHA- MIDE	DOXO-RUBICIN HYDRO- CHLORIDE	5- FLUORO- URACIL	METHO- TREXATE	ETOPOSIDE	PACLITAXEL	THIOTEPA
>480	>480	>480	>480	>480	>480	>480	>480	>480

TO ORDER

Re-Order	Chest	Height	Size
S-BDLC-S	84-92cm (33"-36")	164-170cm (5'4"-5'6")	S
S-BDLC-M	92-100cm (36"-39")	170-176cm (5'6"-5'9")	M
S-BDLC-L	100-108cm (39"-42")	176-182cm (5'9"-6'0")	L
S-BDLC-XL	108-116cm (42"-45")	182-188cm (6'0"-6'2")	XL
S-BDLC-XXL	116-124cm (45"-48")	188-194cm (6'2"-6'4")	XXL

Packing

One piece per sealed inner PE bag; one inner bag per sealed outer PE bag; 30 outer bags per lined carton (30 pieces)

CONTACT

Europe (Headquarters)

Nitritex Ltd.
Minton Enterprise Park,
Oaks Drive,
Newmarket, Suffolk,
CB8 7YY,
United Kingdom
T: +44 (0) 1638 663338
F: +44 (0) 1638 668890
E: europa@bioclean.com

Other Regions

Asia: malaysia@bioclean.com
Americas: americas@bioclean.com



BioClean™ is a brand of Nitritex Ltd.

For more information, please visit www.bioclean.com

S-BDLC/1608/PDS12