



# C1 Wipe

Hydroentangled polyester/cellulose wipe

## Description

The C1 Wipe is constructed using nonwoven fibers which are hydraulically entangled into fabric using a blend of 45% polyester and 55% cellulosic fibers. The C1 Wipe is an excellent all-purpose wipe for less critical, nonabrasive applications. It has an outstanding absorbency due to their cellulosic content. Strong, durable, and extremely absorbent, these wipes are excellent for wiping and absorbing spills. Features low levels of particles and extractables.

## Technical Data

Attribute; (units)	Value **	Test Method
Basis weight; (g/m <sup>2</sup> )	68	
Sorbency in water		
Intrinsic; (mL/g)	4.82	IEST-RP-CC004.2, Sec. 7.1
Extrinsic; (mL/m <sup>2</sup> )	335	IEST-RP-CC004.2, Sec. 7.1
Sorptive rate; (seconds)	<1	
Non-volatile residue, NVR		IEST-RP-CC004.2, Sec. 6.1.2
In deionized water; (g/m <sup>2</sup> )	0.056	
In isopropanol; (g/m <sup>2</sup> )	0.015	
Specific ions		IEST-RP-CC004.2, Sec. 6.2.2
Sodium; (ppm)	11.2	
Chloride; (ppm)	7.8	
Particles, readily releasable		IEST-RP-CC004.2, Sec. 5.1
P ≥ 0.3μm; (x10 <sup>6</sup> /m <sup>2</sup> )	n/a	
P ≥ 0.5μm; (x10 <sup>6</sup> /m <sup>2</sup> )	17.1	
Fibers > 100μm; (x10 <sup>3</sup> /m <sup>2</sup> )	14.8	IEST-RP-CC004.2, Sec. 5.2

\*\* ND = None detected; levels are below detection limit of test equipment

Part Number	Description	EA/OB1	OB1/OB2	OB2/CS	EA/CS
C1-99	C1 Wipes, 9" x 9" (23 x 23cm)	300	1	12	3600
C1-1212	C1 Wipes, 12" x 12" (30 x 30cm)	150	1	18	2700
C1Q-1017	C1 Wipes, 10" x 17" (25 x 43cm), quarterfolded	250	1	4	1000
C1-2365985	Mop Cover, 10" x 24" (25 x 60cm)	50	1	10	500

Key: EA = Each, OB1 = Outer Bag 1, OB2 = Outer Bag 2, CS = Case

### Notes:

- 1) The information presented here is applicable to the part numbers shown above as well as to any product containing the same materials and produced under the same conditions, regardless of product size or packaging configuration. Please contact a Contec sales representative for more details.
- 2) Data shown are typical values and should not be used as product specifications.
- 3) Valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions.
- 4) Current and/or comparison data may be available. Please contact a Contec sales representative for details.

Revision date: 02/03/10



Copyright © 2010 Contec, Inc. All rights reserved.

**North America**  
P.O. Box 530  
Spartanburg, SC 29304 USA  
Phone: +1-864-503-8333  
www.contecinc.com

**Europe**  
Zl du Prat – RP 3707  
56037 VANNES Cedex  
FRANCE  
+33 297 437 690

**China**  
No.17 Longyun Road  
Suzhou 215024  
CHINA  
+ 86-512-6274 4050