

# BIOCLEAN™

## SAFESTEP™

Cleanroom Overshoes

# NSO

### About

BioClean SafeStep™ Overshoes have low levels of particle shedding and are processed to ensure ISO Class 5 compatibility. They feature an elastomer coating to ensure good grip and durability.

### Specifications

**TEARING STRENGTH:**

1.6kg (min)

**MATERIAL:**

Elastomer coating over non-woven spunbonded polypropylene

**THICKNESS:**

0.14mm

**LENGTH:**

406mm (16") and 455mm (18").

**COMPATIBILITY:**

ISO Class 5

**CONSTRUCTION:**

Elastomer coating over non-woven spunbonded polypropylene. Tearing Strength: 1.6kg (min).

**COLOUR:**

White

**ISO CLASS 5 COMPATIBLE**

**SLIP-RESISTANT & DURABLE**

**LOW-LINTING**

### Features

- Slip-resistant
- Low levels of particle shedding
- Durable
- Elastomer coating



## Quality Standards

- Manufactured in a facility holding ISO 9001:2008 certification
- Processed in an NEBB certified ISO Class 5 cleanroom environment

## Shelf Life & Storage

Five (5) years from date of manufacture.  
Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light.

## Physical Properties

PRODUCT CODE	LENGTH(±5%)	HEIGHT(±5%)	Conductivity
NSO016	406mm	170mm	N/A
NSO018	457mm	170mm	

## TO ORDER

### Re-order code

### Size

NSO016	16" (406mm)
NSO018	18" (457mm)

### Packing

100 pieces per sealed inner PE bag; one inner bag per sealed outer PE bag; four outer bags per lined carton (400 pieces)

## CONTACT

### Europe

#### (Headquarters)

Nitritex Ltd.  
Minton Enterprise Park,  
Oaks Drive,  
Newmarket, Suffolk,  
CB8 7YY,  
United Kingdom  
T: +44 (0) 1638 663338  
F: +44 (0) 1638 668890  
E: [europa@bioclean.com](mailto:europa@bioclean.com)

### Other Regions

Asia:  
[malaysia@bioclean.com](mailto:malaysia@bioclean.com)  
Americas:  
[americas@bioclean.com](mailto:americas@bioclean.com)



BioClean™ is a brand of Nitritex Ltd.  
For more information, please visit [www.bioclean.com](http://www.bioclean.com)

NSO/1604/PDS21