

BIOCLEAN™

VINYL TAPE

Cleanroom Tape

S-BVCT

About

BioClean Vinyl Cleanroom Tape is ideal for general cleanroom use, with good abrasion resistance, excellent durability and zero residue. Packed and processed to ensure ISO Class 4 compatibility.

Specifications

MATERIAL:

Vinyl with PET Laminate

THICKNESS:

Film: 100µm Adhesive: 30µm

COMPATIBILITY:

ISO Class 4

CONSTRUCTION:

Vinyl with PET Laminate and acrylic adhesive. PE Inner Core.

COLOUR:

White, Blue, Green, Red or Yellow

STERILIZATION:

Gamma irradiation

GOOD ABRASION RESISTANCE

ZERO RESIDUE

EXCELLENT DURABILITY

Features

- Adhesive force (g/25mm): 800g/25mm ±100g
- Good abrasion resistance
- Zero residue
- Excellent durability
- Gamma irradiated
- Double bagged



Quality Standards

- Manufactured in a facility holding ISO 9001:2008 certifications

Sterilization

Method: Gamma irradiation
Minimum Dose: 25kGy

Shelf Life & Storage

Store in a dry, cool place (<40°C) away from direct sunlight and fluorescent light.

TO ORDER

Re-order code

Size

S-BVCT1W	25mm x 33m
S-BVCT2B	12.5mm x 33m
S-BVCT2G	12.5mm x 33m
S-BVCT2R	12.5mm x 33m
S-BVCT2W	12.5mm x 33m
S-BVCT2Y	12.5mm x 33m
S-BVCT3W	50mm x 33m

Packing

S-BVCT1W (White)/ S-BVCT2B (Blue)/ S-BVCT2G (Green)/ S-BVCT2R (Red)/ S-BVCT2W (White)/ S-BVCT2Y (Yellow): One roll per sealed inner PE bag; one inner bag per sealed outer PE bag; 30 outer bags per lined carton (30 rolls)

S-BVCT3W (White): One roll per sealed inner PE bag; one inner bag per sealed outer PE bag; 12 outer bags per lined carton (12 rolls)

CONTACT

Europe

(Headquarters)

Nitritex Ltd.
Minton Enterprise Park,
Oaks Drive,
Newmarket, Suffolk,
CB8 7YY,
United Kingdom
T: +44 (0) 1638 663338
F: +44 (0) 1638 668890
E: europa@bioclean.com

Other Regions

Asia:

malaysia@bioclean.com

Americas:

americas@bioclean.com



BioClean™ is a brand of Nitritex Ltd.

For more information, please visit www.bioclean.com

S-BVCT/1610/PDS10