


	<b>Laboratory and Safety Goggles</b>	
<b>Area of Application and Properties</b>		
<ul style="list-style-type: none"> <li>▪ <b>Maximum protection and wearing comfort:</b> Tested safety goggles manufactured by UVEX Safety, can be autoclaved for laboratories and cleanrooms. Some types are suitable for spectacle wearers. Special non-fogging coating.</li> <li>▪ <b>Application range:</b> Protection against mechanical risks, liquids and coarse dust. Suitable for various uses.</li> <li>▪ <b>Protection capacity:</b> Does not provide protection against high-speed particles, laser beams, temperatures of over 55°C, arcing faults, molten metals (except Item No 121716).</li> <li>▪ <b>Before use:</b> Check for any damage! Do not use goggles if marking is missing or illegible.</li> </ul>		
<b>Types</b>		
	<b>Safety goggles super fit 9178 CR</b>	
<b>Order No.</b>	121706	
<b>Size</b>	Universal	
<b>Colour</b>	Transparent	
<b>Properties</b>		
<ul style="list-style-type: none"> <li>▪ Very light safety glasses</li> <li>▪ Large field of vision</li> <li>▪ Highly flexible frame with XST-technology</li> <li>▪ Suitable for cleanroom use</li> <li>▪ Ideal for use with operating masks</li> <li>▪ Autoclavable up to 121 °C (replace after max. 10 cycles)</li> </ul>		
<b>Frame Marking</b>		
<b>W</b>	Code letter of manufacturer	
<b>166</b>	EN standard	
<b>F (45 m/s)</b>	Mechanical strength	
<b>CE</b>	EC-declaration of conformity	
<b>0196</b>	Number of the notified body	
<b>Lens Marking</b>		
<b>2C-1,2 (DIN EN 170)</b>	Safety level	
<b>W</b>	Code letter of manufacturer	
<b>1</b>	Optical class	
<b>K</b>	Surface resistance – small parts	
<b>N</b>	Resistance against fogging	

DIN	Certification
CE	EC-conformity
0196	Notified body
	<b>Protective goggles 9169 super f OTG CR</b>
Order No.	121711
Size	Universal
Colour	Transparent
<b>Properties</b>	
<ul style="list-style-type: none"> <li>▪ Light safety goggles with complete field of vision</li> <li>▪ Ideally suited for wearers of prescription glasses</li> <li>▪ Specially coated non fogging lens</li> <li>▪ 11° inclined glass for more safety and a better view</li> <li>▪ X-stream technology (XST) – flexible frame systems</li> <li>▪ Can be autoclaved at 121° (replace after max.10 cycles)</li> </ul>	
<b>Frame Marking</b>	
W	Code letter of manufacturer
166	EN standard
F (45 m/s)	Mechanical strength
CE	EC declaration of conformity
0196	Number of notified body
<b>Lens Marking</b>	
2C-1,2 (DIN EN 170)	Safety level
W	Code letter of manufacturer
1	Optical class
K	Surface resistance – small parts
N	Mechanical strength
DIN	Certification
CE	EC-conformity
0196	Notified body



**Safety goggles 9302 500 ultrasonic CR**

<b>Order No.</b>	121716
<b>Size</b>	Universal
<b>Colour</b>	White-transparent

**Properties**






- Antifog coating
- Can be worn over prescription glasses as well as with respiratory masks
- Optical class 1
- Adjustable silicone headband for perfect fit
- Suitable for cleanroom use
- Exceptional ventilation
- Can be autoclaved at 121° (max.10 cycles)

**Frame marking**

<b>3 (Liquid drips &amp; spray)</b> <b>4 (Coarse dust)</b> <b>9 (hot solid materials and melting metals)</b>	Field of use
<b>B (120 m/s)</b>	Mechanical strength
<b>W</b>	Code letter of manufacturer
<b>166</b>	EN standard
<b>CE</b>	EC declaration of conformity
<b>0196</b>	Number of the notified body

**Lens Marking**

<b>2C-1,2 (DIN EN 170)</b>	Safety level
<b>W</b>	Code letter of manufacturer
<b>1</b>	Optical class
<b>B (120/m/s)</b>	Mechanical strength
<b>9</b>	Field of use
<b>K</b>	Surface resistance – small parts
<b>N</b>	Fogging resistance
<b>DIN</b>	Certification mark
<b>CE</b>	EC-conformity
<b>0196</b>	No. of notified body

<b>Care Instructions</b>	
<ul style="list-style-type: none"> <li>▪ <b>Cleaning:</b> Using clean water and household washing-up liquid (no lye, acids or solvents!). Avoid a strong mechanical action when cleaning (scratched surface = high proportion of stray light).</li> <li>▪ <b>Disinfection:</b> Item can be disinfected with any standard disinfectant</li> </ul>	
	<b>CE-Mark</b>
<p>CE-marking in accordance with <b>PPE Directive 89/686/EEC</b> for PPE (category II). The type test performed was based on EN 166. Produced by: UVEX Arbeitsschutz GmbH, Fürth, Germany</p>	
<b>0196</b>	<b>Notified Body „0196“</b>
DIN CERTCO, Gartenstr. 133, D-73430 Aalen, Deutschland.	
	<b>Quality Management System</b>
<p>Our <b>Quality management system</b> is <b>tested and certified</b> by TÜV Product Service GmbH (a certification body accredited by the German Accreditation Council) in accordance with DIN EN ISO 9001:2008. Regular <b>audits and production site inspections</b> guarantee the quality of our products.</p>	
	<b>Storage and Transport Conditions</b>
<ul style="list-style-type: none"> <li>▪ Cool (+10 to +40°C)</li> <li>▪ Dry (humidity max. 65%)</li> <li>▪ No contact with pointed and/or sharp objects</li> </ul>	
	<b>Shelf life</b>
<ul style="list-style-type: none"> <li>▪ 5 years from date of manufacture</li> </ul>	
<b>Manufacturer</b>	
UVEX Arbeitsschutz GmbH, Würzburger Str. 181 – 189, 90766 Fürth, Germany	
<b>Distributor</b>	
	<p>BERNER INTERNATIONAL GmbH Mühlenkamp 6 - 25337 Elmshorn Tel: 04121 4356 0 Fax: 04121 4356 20 info@berner-international.de www.berner-international.eu</p>